

# Frosted Acrylics

Specifications	
<b>Material:</b>	Extruded Acrylic
<b>Finish:</b>	Frosted both sides
<b>Sheet Size:</b>	24" x 48" (610 x 1219mm) +0, -.125"
<b>Thickness 1-Ply:</b>	1/8" (3.2mm) Use 442 as first digits of item code. 1/4" (6.0mm) Use 452 as first digits of item code. <b>Note: Gauges are approximate.</b>
<b>Thickness 2-Ply:</b>	NONE
<b>Thickness 3-Ply:</b>	NONE
<b>Usage:</b>	Interior signage, Exterior signage, Signage component or substrate, ADA compliant (for tactile signage applications)
<b>Engraving Method:</b>	Laser Rotating carbide Router
Capabilities	
<b>Scores</b>	<b>Bonds</b>
<b>Saws</b> ■	■ <b>Permits Fine Engraving</b>
<b>Drills</b> ■	■ <b>UV Stable</b>
<b>Shears</b>	<b>Back-Filling</b>
<b>Laser Vector Cuts</b> ■	■ <b>Back-Lighting</b>
<b>Bevels</b>	■ <b>Braille-Engravable</b>
<b>Heat Bendable</b>	<b>Embosses</b>
<b>Screen Prints</b> ■	<b>Ink Prints</b>
<b>Hot Stamps</b>	■ <b>Thermal Prints</b>