

# Ultra-Mattes Reverse Engravable

Specifications	
<b>Material:</b>	Laminated Impact Acrylic for reverse engraving
<b>Finish:</b>	Matte non-glare
<b>Sheet Size:</b>	24" x 48¾" (610 x 1238mm)
<b>Thickness 1-Ply:</b>	NONE
<b>Thickness 2-Ply:</b>	1/16" (1.6mm) Use 322 as first digits of the item code.
	1/8" (3.2mm) Use 342 as first digits of the item code. <i>[Matte/Clear (322-101) is .052" (1.3mm).]</i>
<b>Thickness 3-Ply:</b>	1/8" (3.2mm) Use 343 as first digits of the item code.
<b>Usage:</b>	Interior signage Exterior signage Tactile signage Personal Identification
<b>Engraving Method:</b>	Rotating Carbide
<b>Cutting Depth:</b>	.012" (.30mm)
Capabilities	
<b>Scores</b>	■ <b>Bonds</b>
<b>Saws</b>	■ <b>Permits Fine Engraving</b>
<b>Drills</b>	■ <b>UV Stable</b>
<b>Shears</b>	■ <b>Back-Filling</b>
<b>Laser Vector Cuts</b>	■ <b>Back-Lighting</b>
<b>Bevels</b>	■ <b>Braille-Engravable</b>
<b>Heat Bendable</b>	■ <b>Embosses</b>
<b>Screen Prints</b>	■ <b>Ink Prints</b>
<b>Hot Stamps</b>	■ <b>Thermal Prints</b>