



ADA AlternativeTM

Appliqué and Substrate

Specifications	
Material:	Single ply modified acrylic
Finish:	Matte non-glare
Sheet Size:	24" x 48¾" (610 x 1238mm)
Thickness 1-Ply:	1/32" (.8mm) Use 311 as first digits of the item code.
	.040" (1.0mm) Use 391 as first digits of the item code.
	1/16" (1.6mm) Use 321 as first digits of the item code.
	1/8" (3.2mm) Use 341 as first digits of the item code.
	<i>ADA Alternative is available with or without adhesive. To order with adhesive, add "8" to the end of the item code.</i>
Thickness 2-Ply:	NONE
Thickness 3-Ply:	NONE
Usage:	Interior signage, Exterior signage, Tactile Signage
Engraving Method:	Laser Rotating carbide
Cutting Depth:	1/4" round .020" tip at 20-25 degree angle.
Capabilities	
Scores	■ ■ Bonds
Saws	■ Permits Fine Engraving
Drills	■ ■ UV Stable
Shears	Back-Filling
Laser Vector Cuts	■ Back-Lighting
Bevels	■ ■ Braille-Engravable
Heat Bendable	■ Embosses
Screen Prints	■ Ink Prints
Hot Stamps	■ ■ Thermal Prints

Some appliqué colors available in 1mm for European regulations.